

2DA3 OIL PRESS. 80#/OIL TEMP. 100-260°F
 2DA3-1 OIL PRESS. 80#
 2DA3-2 OIL PRESS. 0-7 kg/OIL TEMP. 40-120°C
 2DA3-3 OIL PRESS. 100#/OIL TEMP. 100-260°F
 2DA3-5 OIL PRESS 80#/FUEL PRESS. 16#
 2DA3-6 PRESSURE 100#/TEMPERATURE 100-260°F
 2DA3-7 WATER TEMP. 100-260°F
 2DA3-8 AIR TEMP. -50 to +50°C/CARB TEMP. -50 to +50°C
 2DA3-9 AIR TEMP. -50 to +50°C/VOLT 7-17
 2DA3-10 CARB TEMP. -50 to +50/VOLT 7-17
 2DA3-12 OIL PRESS 16#/OIL TEMP. 100-260°F
 2DA3-14 TEMP. (T trans, 100-400°F and C coolant 100-260°F)
 2DA3-15 TEMP. (T trans. 100-400°F and O oil, 100-260°F)
 2DA3-16 TEMP 100-260°F
 2DA3-19 TEMP 100-400°F and 100-260°F
 2DA3-21 Inter cooler temp, in-out 50-325°F
 2DA3-25 CARB TEMP -50 to +50°C
 2DA3-27 Inter cooler temp., in-out 120-400°C
 2DA3-28 TEMP 50-325°F
 2DA3MS OIL PRESS 80#/OIL TEMP 100-260°F
 req. press sender #387-11MS
 2DA3-1MS OIL PRESS 80#
 req. 2 #387-11MS press. senders
 2DA3-2MS OIL PRESS 0-7kg/OIL TEMP 100-260°F
 req. press. sender #387-11MS
 2DA3-3MS OIL PRESS 100#/OIL TEMP 100-260°F
 req. press. sender #387-11MS
 387-11MS Press Sender
 2DA3-5MS OIL PRESS 80#/FUEL PRESS 16#
 req. press senders #387-11MS & #387-13MS
 2DA3-6MS PRESS 100#/TEMP 100-260°F
 req. press sender #387-11MS
 2DA3-12MS OIL PRESS 16#/OIL TEMP 100-260°F
 req. press sender #387-13MS
 2DA3-13MS AIR PRESS 100# req. 2 press send. #387-11MS
 2DA3-17MS PRESS 80#/TEMP 100-260°F
 req. press sender #387-11MS
 2DA3-18MS FUEL PRESS 16#
 req. 2 press senders #387-13MS
 2DA3-20MS PRESS 16#/TEMP 100-260°F
 req. press sender #387-11MS
 2DA3-22MS PRESS 80#/VOLT 6-16
 req. press sender #387-11MS
 2DA3-23MS PRESS 16#/VOLT 6-16
 req. press sender #387-13MS
 2DA3-24MS FUEL PRESS 16#/OIL PRESS 100#
 req. press sender #387-13MS
 2DA3-26MS OIL PRESS 100#/FUEL PRESS 80#
 req. 2 press senders #387-11MS
 387-13MS pressure sender
 387-11MS pressure sender
 2DA4 FUEL LEVEL 240 ohm
 2DA4-4 FUEL LEVEL 90 ohm
 2DA4-5 FUEL LEVEL 30 ohm full/0 ohm empty
 2DA4-6 FUEL LEVEL 20 ohm
 2DA4-7 FUEL LEVEL 240 ohm/VOLT 7-17
 2DA4-9 FUEL LEVEL 78 ohm
 2DA4-10 FUEL LEVEL 0 ohm full/30 ohm empty
 2DA4-18 FUEL LEVEL 240 ohm/AMP -60 to +60
 req. shunt #237-3
 2DA4-19 FUEL LEVEL 240 ohm/AMP -30 to +30
 req. shunt #237-2
 2DA4-1MS FUEL LEVEL 240 ohm/FUEL PRESS 16#
 req. press sender #387-13MS
 2DA4-3MS FUEL LEVEL 30 ohm AC/FUEL PRESS 16#
 req. press sender #387-13MS

3-1/8" QUAD INSTRUMENTS

3AQ1 CHT 100-700°F
 3AQ2 EGT 600-1600°F
 3AQ3 CHT 100-700°F/EGT 600-1600°F
 CHT 100-700°F/EGT 600-1600°F
 3AQ7 CHT 100-700°F/RPM 0-3500
 EGT 600-1600°F/VOLTS 6-16
 #186-12A2L Light Kit for QUAD INST.
 3AQ4MS OIL PRESS 100#/EGT 60-1600°F
 OIL TEMP 100-260°F/CHT 100-700°F
 req. press sender #387-11MS
 3AQ5MS OIL PRESS 100#/VOLTS 6-16
 OIL TEMP 100-260°F/CHT 100-700°F
 req. press sender #387-11MS
 3AQ6MS OIL PRESS 100#/VOLTS 6-16
 WATER TEMP 100-260°F/RPM 1K-7K
 req. press sender #387-11MS
 3AQ8MS FUEL LEVEL 90 ohm/EGT 60-1600°F
 FUEL LEVEL 90 ohm/FUEL PRESS 16#
 req. press sender #387-13MS

3-1/8" DUAL EGT AND CHT

3DA1 EGT 70-1700°F/CHT 100-800°F
 3DA1-1 EGT 400-1600°F/CHT 100-800°F
 3DA1-2 EGT 350-950°C/CHT 0-450°C
 3DA2 EGT 700-1700°F
 3DA2-1 EGT 400-1600°F
 3DA2-2 EGT 200-800°C
 3DA2-3 EGT 100-1800°F
 3DA2-4 EGT 400-900°C
 3DA8 CHT 100-800°F
 3DA8-2 CHT 0-350°C
 3DA2-10 EGT 800-1500°F, uses only sender #712-2DWK
 3DA2-11 EGT 1000-2000°F, uses only sender #712-2DWK

3-1/8" TRIPLE SQ. STYLE DIST.

A3T1 CHT 100-700°F
 A3T2 EGT 400-1400°F
 A3T3 EGT 400-1400°F/CHT 100-700°F/
 CARB TEMP -50 to +50°C
 A3T7 FUEL LEVEL 240 ohm/RPM 1K-7K/
 VOLTS 6-16
 A3T8MS OIL PRESS 80#/OIL TEMP 100-260°F/
 FUEL PRESS 16#, req. press senders
 #387-11MS and #387-16MS
 A3T9MS OIL PRESS 100#/FUEL PRESS 80#/
 OIL TEMP 100-260°F, req. press
 senders #387-11MS and #387-13MS
 A3T10MS CHT 100-700°F/OIL PRESS 80#/
 OIL TEMP 100-260°F, req. press
 sender #387-11MS

3-1/8" SQUARE STYLE QUAD A/S KITS

K3AQ3-3H CHT/MPH/EGT/RPM
 altn. 2 pole
 K3AQ3-2H CHT/MPH/EGT/RPM
 'R' 1 & 2 imp.
 100-700°F/0-70/600-1600°F/1K-7K RPM
 693A bullet case w/323 mount, w/303GW
 sender w/323 mount & 510A-1 propeller
 w/712-2DWK EGT sender, w/712-4W CHT sender
 cables: sing. strand 4' long blue
 sing. strand 4' long brown
 2 conductor 4' long blk & white
 6 conductor 6' long